



Automatic Rotary Brush Sander



Model: SL-RB

★門板的高低落差超過 18mm , 這台機器是最佳選擇 ! The doors that profile depth more than 18mm, this machine is best choice

★履帶式砂光頭能夠涵蓋整個門板,加上旋轉盤的設計,使砂光的範圍更加廣大,不會遺漏任何死角!

The rotational sanding head with a large sanding area ensures a consistent sanding in all work piece areas!

★吸力穩固的真空系統,即使是小型工件,也能穩固在輸送帶上! a perfect vacuum system guarantees that even small work pieces can be feed surely!



★適當的打磨速度, 減少砂布的損耗速度, 延長使用的壽命
Large abrasives quantities make low movement speeds possible, at better effectiveness.

★方便快速更換砂布絲條

It's very easy and convenient to replace the brush wear strip

★This machines install "Double Side Sanding strip", can sanding raw sanding and sealer sanding on the same time don't need to change the Sanding paper. so that will fit customer requirement

機器上是裝設"雙面砂布絲+木棕刷",可以選擇不同粗細的砂紙.

不論是白胚砂光(上漆前)或是底漆砂光 都可以使用在一台機器



and



SPECIFICATIONS:

機器型號 Model:	SL-1100RB	SL-1350RB
最大工作寬度 Max.Working Width	1100mm	1350mm
最小工作物尺寸 (真空系統)	100mm × 160mm	100mm × 160mm
Min.Work-pieces for Vacuum		
最小工作物 Min. Work-pieces Thickness	5mm	5mm
履帶式砂光頭 Track type Head	ЗНР	3НР
旋轉盤 Carousel Motor	ЗНР	3НР
輸送床台 Conveyor Motor	5HP	5HP
真空系統 Vacuum Motor	15HP + 15HP	15HP + 15HP
履帶砂光頭轉速 Speed of Track type Head	100~250 RPM	100~250 RPM
旋轉盤轉速 Carousel rotary RPM	2~10	2~10
輸送帶速率 Variable Feeding Speed	2 ~ 12 M/min	2 ~ 12 M/min